

Product data sheet

PL 55 *



Glass Fitting manual locking device fitting with round bolt

AREAS OF APPLICATION

- For full-glass doors
- For glass thicknesses 10 and 12 mm
- For single-action and double-action doors
- For internal and external systems
- Suitable for single and double leaf swing doors

PRODUCT FEATURES

- Elegant cover caps made of polished or brushed stainless steel
- Problem-free adjustment to glass thicknesses of 10 – 12 mm

TECHNICAL DATA

Productname	PL 55 *
Dimensions	102 x 32 x 96 mm
Width	32 mm
Length	102 mm
Height	96 mm
Glass thickness (min.)	10 mm
Glass thickness (max.)	12 mm
Type of installation	Glass installation

VARIANTS / ORDER INFO

Designation	Description	Ident-No.	Colour	Dimensions	Glass thickness
GEZE Glass Fitting PL 55 *	Fitting for manual locking device, with round bolts	180485	Polished stainless steel	102 x 32 x 96 mm	10 – 12 mm
GEZE Glass Fitting PL 55 *	Fitting for manual locking device, with round bolts	169769	Satin stainless steel	102 x 32 x 96 mm	10 – 12 mm

ACCESSORIES

GLASS FITTING ROUND BOLT STRIKE *

Closing recess for round bolts



Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
GEZE Glass Fitting Round bolt strike *	Closing recess for locking fittings with round bolts	169778	Satin stainless steel	74.5 x 25 x 19 mm	Floor, Ceiling, Wall
GEZE Glass Fitting Round bolt strike *	Closing recess for locking fittings with round bolts	180493	Polished stainless steel	74.5 x 25 x 19 mm	Floor, Ceiling, Wall

GLASS FITTING SQUARE BOLT STRIKE *

Strike plate for locking fittings with square bolt



Designation	Description	Ident-No.	Colour	Dimensions	Type of installation
GEZE Glass Fitting Square bolt strike	Strike plate for locking fittings with square bolt	180494	Polished stainless steel	90 x 2.5 x 23 mm	Floor, Ceiling, Wall
GEZE Glass Fitting Square bolt strike *	Strike plate for locking fittings with square bolt	169779	Satin stainless steel	90 x 2.5 x 23 mm	Floor, Ceiling, Wall

* The products designated above may vary in form, type, characteristics, function, or availability depending on the country. Please get in touch with your GEZE contact person if you have any questions.